

FT-AS20018XHK

Camera

Image Sensor: | 2MP Progressive Scan CMOS

Effective Pixels: | 1920(H)x1080(V)

Signal System: | IP

White Balance: | Auto

AGC: | Auto/Manual

BLC: | Support

Focal Length: | 5-90MM, 18X

Signal Transfer: | IP

Pan & Tilt

Rotation Range: | Pan 360°, vertical 90°, Auto Flip 180°

Rotation Speed: | Manual speed 80°/s

Preset Points: | 256pcs preset(Dwell time 01-60s interval available)

Guard Tours: | 4 groups (Each group 16 preset, dwell time and speed selectable)

AB scan range: | Any point in Pan range: 0°~360°

AB scan speed: | 1-9 grades

Infrared

IR irradiation distance: | 150m

LEDs: | 8Pcs laser LED

Support Ambient Light
Detection: | IR illumination on 1-9 Grads selectable

General

RS-485 Protocols: | Pelco-P, Pelco-D

Menu Language: | English

Power Supply: | 12V DC

Power Consumption: | $\leq 10W$

Lightning Protection: | Transient voltage 6000V

Working Temperature/H
umidity: | $-15^{\circ}C \sim +60^{\circ}C$

Dimensions: | 30*30*42cm

Weight (approx.): | 10 KG
