

FT-FSBHY400

Image Sensor:		4MP CMOS Image Sensor
---------------	--	-----------------------

Signal System:		PAL NTSC
----------------	--	------------

Effective Pixels:		1305(H)x977(V)
-------------------	--	----------------

Min. Illumination:		0.1 Lux @ (F1.2, AGC ON) 0.3 Lux @ (F2.3, AGC ON)
--------------------	--	--

Shutter Time:		1/25(1/30) s to 1/10,000 s
---------------	--	----------------------------

Lens:		3.7mm Taper Pinhole Lens
-------	--	--------------------------

Lens Mount:		M12
-------------	--	-----

Adjustment Range:		Pan: 0 - 360°, Tilt: 0 - 75°, Rotation: 0 - 360°
-------------------	--	--

Day& Night:		IR cut filter with auto switch
-------------	--	--------------------------------

Video Frame Rate:		720p@25fp 720p@30fps
-------------------	--	-------------------------

HD Video Output:		AHD TVI CVI Output Optional
------------------	--	---------------------------------

Synchronization:		Internal Synchronization
------------------	--	--------------------------

S/N Ratio:		More than 62 dB
------------	--	-----------------

Up the Coax: | Support

Operating Conditions: | -20 °C - 60 °C (-20 °F - 140 °F)
Humidity 90% or less (non-condensing)

Power Supply: | 12 VDC±15%

Power Consumption: | Max. 4W

Dimension: | 69(W) x 126(H) x 50(D)mm

Weight: | 550g
